



## KGD-塑料卡箍轴承 Plastic Collar Bearings

### 订购编码 Order PN

KGD-05-12

 高度 High  
 内径 Inner diameter


座孔 Housing: H7 轴 Shaft: h9

订购编码 Order PN	d <sub>1</sub> [mm]	公差 Tolerance [mm]	d <sub>2</sub> [mm]	d <sub>3</sub> [mm]	d <sub>4</sub> [mm]	S <sub>0.10</sub> [mm]	b <sub>1</sub> <sup>+0.20</sup> [mm]
KGD-03-02	3	+0.020/+0.080	4.2	4.8	6	0.6	3.2
KGD-04-02	4	+0.030/+0.105	5.2	5.9	7	0.6	3.2
KGD-05-02	5	+0.030/+0.105	6.2	6.8	8	0.6	3.2
KGD-05-03	5	+0.030/+0.105	6.2	6.8	8	0.6	4.2
KGD-06-02	6	+0.030/+0.105	7.2	7.8	11	0.6	3.2
KGD-06-03	6	+0.040/+0.130	7.2	7.8	11	0.6	4.2
KGD-08-02	8	+0.040/+0.130	9.6	10.4	13	0.8	3.6
KGD-08-03	8	+0.040/+0.130	9.6	10.4	13	0.8	4.6
KGD-10-014	10	+0.040/+0.130	11.6	12.4	15	0.8	3
KGD-10-02	10	+0.040/+0.130	11.6	12.4	15	0.8	3.6
KGD-10-025	10	+0.040/+0.130	11.6	12.4	15	0.8	4.1
KGD-10-03	10	+0.050/+0.160	11.6	12.4	15	0.8	4.6
KGD-12-02	12	+0.050/+0.160	13.6	14.4	17	0.8	3.6
KGD-12-025	12	+0.050/+0.160	13.6	14.4	17	0.8	4.1
KGD-12-03	12	+0.050/+0.160	13.6	14.4	17	0.8	4.6
KGD-14-03	14	+0.050/+0.160	15.6	16.4	19	0.8	4.6
KGD-16-02	16	+0.050/+0.160	17.6	18.4	21	0.8	3.6
KGD-16-03	16	+0.050/+0.160	17.6	18.4	21	0.8	4.6
KGD-18-03	18	+0.050/+0.160	20	21	23	1	5
KGD-20-03	20	+0.065/+0.195	22	23	25	1	5
KGD-25-03	25	+0.065/+0.195	27	28	30	1	5

\*d<sub>1</sub> 公差为压入标准 H7 座孔 (ISO3547-1) 后公差\*Tolerance d<sub>1</sub>: after being pressed into housing H7 (ISO3547-1)

### KGD塑料卡箍轴承安装方式 Plastic Clip Bearings Installation Method



Step: 1



Step: 2



Step: 3

易用手装配 Easy assembly by hands